




SIGN-TOPPERS

SIMPLY BETTER L.E.D. DISPLAYS

LED SIGN Order Detail		HEIGHT	3	WIDTH	8	Total single side(sq. ft)	24	Total double side(sq. ft)	48		
SINGLE SIDED 3' x 8'											
Item	Picture	Product Detail			Brand	Quantity		CABINETS	Total/USD		
Product		Product Type	P6.35 LED SIGN			SIGN-TOPPERS	4	CABINETS	2' x 3'		
		Display Size(Ft)	Height(ft):	3	Width(ft):						8
		Module Size	12in x 12in								
		Cabinet Material	Aluminium waterproof cabinet for front service with locker								
		Led Lamp	Gold Wire Lamp								
		Resolution	Width(dots):	384	Height(dots):						144
		Single Side or Double Side	Double Side								
Control System		Novastar controller TB30 WIFI +4G			Novastar	1	piece		Included		
		Novastar Receiving card MRV412			Novastar	8	piece		Included		
Spare Part		Backup p6.35 smd outdoor display module Module size is:12in x 12in			12' x 12' MODULES	2	piece		included		
		Backup p6.35 smd outdoor display module Module size is:12in x 12in			12' x 12' MODULES	2	piece		Included		
		Novastar Receiving card MRV412			Novastar	1	piece		included		
		Xingxu power supplier UL 100-240V			xingxu	1	set		included		
		Power cables with two male connectors			POWER CABLE	3	set		included		
Package		Wooden case for Led Sign			SHIPPING	1	piece		included		

Product Technical Information

LED Module	Pixel pitch	6.35mm
	Pixel configuration	1RGB
	LED type	SMD2727 Nationstar Gold Wire lamp
	LED module size	12in x 12in
	LED module resolution	48 x 48
	Pixels per sqm.	24800 pixels
	LEDs qty. per sqm.	24800 pcs
	Display refresh rate	1920 Hz
	Scan mode	1/6 scan
	Brightness	10000cd/sqm
	Viewing angle	Horizontal: 140° Vertical: 140°



Cabinet	Cabinet type	Aluminium waterproof cabinet
	LED cabinet dimension	Width: 609.6mm Depth:1219.2mm
	LED cabinet weight	23kg/m2
	Ingress Protection	IP65/IP65
	Serviceability	Front service with locker
	Components in cabinet: Modules, Supply power, Receiving card, cables.connector	













Power supply	Power consumption (max.)	650 watts/sqm
	Power consumption (average.)	150 watts/sqm.
	Input voltage	AC 110V -220V +/- 10%

Operation	Storage environment	Temperature: -40℃ ~ 60℃ Humidity: 10% ~ 85% RH
	Operating environmmt	Temperature: -20℃ ~ 50℃ Humidity: 10% ~ 90% RH
	Lifespan (typical)	≥100,000 hours
	MTBF	≥10,000 hours
	Source compatibility	CVBS, YC, YUV, RGB, DVI, SDI, HD-SDI, HDMI



Payment Terms and Warranty	1. This price is valid for 30 days.
	2. Payment terms: financing available or cash deposit 75% down
	3. Delivery terms: FOB or EXW
	4. Packing: Wooden case.
	5. Lead time: 15-25 days after receiving deposit.
	6. Warranty:5 years
	7. On site installation not included in price.
	8. Support 24-hours remote engineer service support
	9. Support 24-hour quotation service

Installation Technical Information

Installation Method					
	SIDE AND BOTTOM BRACKETS	HOLES AND BRACKETS	SIDE BRACKETS		
					
	WALL GUSSETS	VERTICAL ANGLES	HORIZONTAL ANGLES		
					
	SIDE HOLES	SIDE AND BOTTOM HOLES	THRU POLE SINGLE (POLE OPTIONAL)		
					THRU POLE - DOUBLE (POLES OPTIONAL)
					PROVIDED SEPARATELY THRU POLE - POLE COVER (POLES OPTIONAL)

1 SET Single Sided Displays 3X8				
Power Parameters	The Access Voltage is 200-240V	Single Side Led Sign	Power consumption (max.): 1440W	Power consumption (average.): 480W
		Double Side Led Sign	Power consumption (max.): 2880W	Power consumption (average.): 960W
	The Access Voltage is 100-110V	Single Side Led Sign	Power consumption (max.): 1800W	Power consumption (average.): 600W
		Double Side Led Sign	Power consumption (max.): 3600W	Power consumption (average.): 1200W
Breaker and power cable Infortation	The Access Voltage is 200-240V	Double Side Led Sign		2 set 20amp breaker 2 main power cable
	The Access Voltage is 100-110V	Double Side Led Sign		2 set 30amp breaker 2 main power cable

Product Description

- Angle Iron for Easy installation on to brackets or other support structure
- All-aluminum cabinets for strength and rigidity
- Optional cabinet colors. Front maintenance design, you can use a T-type wrench to quickly maintain the LED SIGN
- Edge-to-edge display area for maximum LED message size
- Support remote sending of programs and provide strong WIFI coverage (range: >165FT)
- Internal USB connection for backup communication and diagnostics
- Ultra-bright, replaceable LED Modules rated at 100,000 hours at full brightness
- Low energy consumption High-strength heat dissipation design
- Solid-state fanless controller internal for maximum weatherabilty
- Optional cellular connection through Verizon 4G LTE Programs can be sent anywhere

Contact Information